

# 14-4C

## PRODUCT SPECIFICATIONS

**Description:** 14/4 High Strand Audio Cable, unshielded with an Overall PVC Jacket  
**Ratings/Approvals:** NEC Article 725, UL Subject 13, Type CL3, (ETL)US, RoHS Compliant  
**Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

---

---

### CONSTRUCTION

Conductor:	14 AWG Bare Copper (OF)
Stranding:	105 x 34
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.012 in. (0.304 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.018 in. (0.457 mm.) Nominal
Overall Cable Diameter:	0.270 in. (6.858 mm.) Nominal
Approx Cable Weight /1,000 ft.:	71 lbs.

---

---

### ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	150 V, RMS
Insulation Colors:	Black, Red, Green, White
Temperature Rating:	-20°C to +75°C