

PRODUCT SPECIFICATIONS

22-2-SR-WH-350

SECURITY CABLE

DESCRIPTION:

- Stranded bare copper conductors.
- HDPE Insulation.
- Cabled conductors
- Flame retardant PVC Jacket
- Flammability : CL2/CM

APPLICATION:


Connection in surveillance systems.

OPERATING TEMPERATURE:

- 10°C to 60°C

MARKING:

2 COND 22 AWG TYPE CM OR CL2 PER UL 444, UL 13, UL 1685 & NEC c(ETL)us CMG - CMX OUTDOOR OR (ETL)us CL2 SUN RES 3164364 #####FT FECHA A B C D E 1 2 3 4 5 6 7 8 9 0
--> GRABADO SECUENCIAL DE 2 EN 2 CADA 2 PIES, EJ: 00000FT ..00002FT ...
FECHA --> mm/aa (MES/AÑO. MES EN INGLES. EJ: AUG/2006)



SPECIFICATIONS:

UL-13

CERTIFICATION:

Sistema de Calidad ISO-9001.

MECHANICAL AND ELECTRICAL CHARACTERISTICS

Conductor	MU	Nominal
Material	Bare copper	
No. of strands	7	
Strand gauge	AWG	30
Conductor Diameter	mm	0.74
Conductor gauge	AWG	22

Insulation	MU	Nominal
Material	HDPE	
Insulation thickness	mm	0.16
Insulation diameter	mm	1.07
Color code	Black-red	

Core	MU	Nominal
No. of conductors	2	
Core assembly	Cabling	

Jacket	MU	Nominal
Material	PVC	
Color	White	
Thickness	mm	0.35
Diameter	mm	2.68

Packaging	MU	Nominal
Material	Plastic bag	
Length	ft	350
Cable weight	Kg/Km	10.8
Packing weight	Kg	1.2

Electrical characteristics	MU	Nominal
Conductor resistance d.c.	Ohm/km	52.55
Insulation resistance	Mohms/K	500

866.839.9187

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.