



CS-HDC5EXTD

HDMI®

Dual CAT5/6 Extender



Signal Inputs/Output

Input Video Signal..... 5 Volts p-p (TTL)
Maximum Single Link Range 1920x1080p
Output Video HDMI1.2a
HDMI Input/Output Connector Type A 19 pin

Operating Frequency

Vertical Frequency Range..... 50/60Hz
Video Amp Bandwidth 1.65Gbps/165MHz

Resolutions(HDTV)

Interlaced(50&60Hz) 480i,576i,1080i
Progressive(50&60Hz)..... 480p,576p,720p,1080p

Mechanical 1.8" W x 1" H x 3.2" D

Size(H-W-D) 45mmW x 25mmH x 81mmD

Weight(Net)..... 0.246KGs

Warranty

Limited Warranty..... 1 Year Parts and Labor

Environmental

Operating Temperature 0° C to +70° C
Operating Humidity..... 10% to 85 % RH
(no condensation)
Storage Temperature..... -10° C to +80° C
Storage Humidity 5% to 90 % RH
(no condensation)

Power Requirement

External Power Supply 5V DC@2A(optional)
Power consumption (Max) 5W

Regulatory Approvals

Converter Unit..... FCC,CE,UL
Power Supply..... UL,CE,FCC