

DETACHABLE FIBER HDMI® CABLES

InstallBay
INSTALLATION HARDWARE

CELEBRATING
70
YEARS
OF INNOVATION



INSTALL BAY DETACHABLE FIBER HDMI® CABLES



SALES 866-839-9187

IB-HDAOCD-030 - 30'
IB-HDAOCD-035 - 35'
IB-HDAOCD-050 - 50'
IB-HDAOCD-065 - 65'
IB-HDAOCD-080 - 80'
IB-HDAOCD-100 - 100'
IB-HDAOCD-130 - 130'
IB-HDAOCD-200 - 200'
IB-HDAOCD-260I - 260'

PRODUCT OVERVIEW

These installer-friendly HDMI cables with Ethernet have a removable headshell with a small connector cover and hook that makes pulling the cable through conduit easy! The hybrid active optical fiber technology supports up to 24Gbps (4x6Gbps) bandwidth for 4K@60Hz and HDR with no external power required. The thin cable diameter and 24K gold plated connector offer beauty and performance for an unbeatable value. Compatible with audio return channel (ARC) electronics and HDMI 2.0. The durable CL3 jacket is designed for in-wall installation and is a home builder's top choice for pre-wiring new homes thanks to their UL-rated jacket that doesn't split or break in colder temperatures*. Available in spools for lengths from 30 to 260 feet.

- 24Gbps (4x6Gbps) speed performance
- Supports 4K@60Hz HDR
- High-speed HDMI 2.0
- 24K gold plated connector
- No external power required
- Detachable head shell reveals small connector easy for pulling through conduit
- Includes connector cover with hook for pulling through conduit
- Durable CL3 jacket for in wall installations
- Audio return channel (ARC)
- Ethernet
- *Operating temperature -10-50 °C / 14 - 122 °F
- *Storage temperature -20-60 °C / -4 - 140 °F

